

ULTRArmor



CHARACTERISTICS & TECNICAL DATA SHEET

• % Solids by Weight:	26%
• Pencil Hardness (ASTM D 3363):	2H
• QUV (ASTM D G-53):	2500 Hours with no gloss loss
• WT./Gal:	7.8
• Coverage:	200 to 300 SqFt/Gal @ 2mil DFT
• VOCs:	> 470 G/L

1 MANUFACTURER

Product Name : SUPREME PAINT + PREMIER IN ONE
Supplier: PINTURAS TONNER Y CIA LTDA
Address: Calle 8 No. 6-11 Entrada 3-Cazucá
Soacha - Bogotá - Colombia
Telephone No: (571) 7803299
Fax No: (571) 7772251



2 RECOMMENDED USES

Ultrarmor is a water clear, solvent-based sealer designed to protect and beautify interlocking brick pavers, concrete floors, and Texture Deck. Cobble Coat is made from 100% acrylic resins and is higher in solids than most conventional concrete sealers. Ultrarmor provides water and UV light resistance with unusually good adhesion to a variety of substrates.

3 APPLICATIONS

Use Ultrarmor on driveways, patios, pool decks, parking lots, walkways, etc. constructed of:

- Concrete Pavers
- Concrete
- Natural Stone

Ultrarmor is not recommended for pavers installed over a solid surface or on surfaces where moisture is unable to dissipate.

4 PROPERTIES & SPECIAL FEATURES

- Easy to apply.
- Industry standard for years.
- Stabilizes joint sand between pavers.
- Inhibits mold, weeds and ant hills.
- Top coat for sealers and surface treatments such as Col- oron, Antique Stain & Texture Deck.

5 DIRECTIONS

Before You Begin: Surfaces must be clean and free of any contaminants before sealing. Cobble Coat's performance is directly related to how thoroughly the surfaced is prepared.

All grease, oil and potential contaminates must be removed.

Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to ensure desired results.

Surface Preparation: Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully.

Cobble Clean, Cobble Prep and Cobble Oxhide may be used for specific cleaning situations.

Mixing Instructions: Stir product.

Application Roller: Apply with a 3/8" to 3/4" nap roller cover.

Avoid over rolling. Always maintain a wet edge.

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line.





5 DIRECTIONS (CONTINUED)

On Bare Surface: One and sometimes two thin coats (2 dry mils) provide the best results on uncoated surfaces.

Previously Sealed: One coat is recommended. Do not apply Ultrarmor more frequently than every 18 months to avoid a build up of sealer.

6 PACKAGING

SIZE	PACKAGE	PER CASE	UNITS/PALLETS
1 GALLON	PAIL	4	148
5 GALLON	PAIL	N/A	36

8 pounds per 1 gallon pail, 45 pounds per 5 gallon pail

7 COVERAGE

1 gallon covers 200 to 300 square feet per coat. Coverage will depend on surface porosity, joint width, and method of application.

Second coat will take slightly less product.

8 CURING INFORMATION

Dry To Touch: 1 Hour

Recoat: 4 Hours

Full Cure: 48 Hours

9 STORAGE & SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 24 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10 MAINTENANCE

Ultrarmor is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

11 MAINTENANCE

Land and sea: Not Regulated Packing Group: III

Flash Point: >114F

12 CLEAN UP

Clean sprayer and tools with SurfaceLogix Reducer immediately after use. Leave Reducer in the line of machine after flushing with water.

13 HEALTH HAZARD INFORMATION

Eye Contact: Wear Eye Protection. May irritate eyes. If in eyes, flush with water for at least 15 minutes.

Inhalation: Use a NIOSH approved respirator.

Ingestion: If swallowed, DO NOT induce vomiting.

Seek medical attention.

Skin: Avoid prolonged contact with skin.

Use with adequate ventilation.

Coated surfaces may become slippery. SurfaceLogix non-skid additive should be incorporated in this situation. However, it is the sole responsibility of the applicator to determine whether a non-skid additive is appropriate for the job.

14 TECHNICAL SUPPORT

For friendly, knowledgeable and courteous technical support please call 7864429366

You may also reach us by sending a query from our website at www.ultrarmor.com

15 DISCLAIMER

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.

Ultrarmor is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.