



TECNICAL DATA SHEET

Vehicle Type	Vinyl Acrylic Latex
Pigment Type	Titanium Dioxide
Volume Solids	40.0%
Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.
Viscosity	105 ± 2 KU
Gloss / Sheen Flat	(1 – 3.5 @ 85°)
Surface Temperature at Application	Min. 50°F – Max. 90°F
Storage Temperature	Min. 40°F – Max. 90°F

- RECOMMENDED FILM THICKNESS – WET 3.8 MILS – DRY 1.5 MILS DEPENDING ON SURFACE TEXTURE AND POROSITY.
- DRY TIME @ 77° F (25°C) @ 50% RH – TO TOUCH 1 HOUR – TO RECOAT 1-2 HOURS
PAINTED SURFACES CAN BE WASHED AFTER TWO OR THREE WEEKS.
- HIGH HUMIDITY AND COOL TEMPERATURES WILL RESULT IN LONGER DRY, RECOAT AND SERVICE TIMES.

1 GENERAL DESCRIPTION

A premium quality, easy to apply Vinyl acrylic coating in a flat finish with excellent hide, Highly washable, durability and spatter resistance. It features fast dry, soap and water cleanup, with no unpleasant paint odor. An elegant flat finish for different surfaces, ceilings and low traffic areas. This paint is self priming on most substrates. Recommended for Limitations Residential or commercial applications where a premium quality flat finish is desired. New or previously painted wallboard, plaster, masonry, or wallpapered surfaces; primed or previously painted wood or metal. Easy application, clean up and touch up. Low odor and provides a mildew resistant coating.

2 PRODUCT DETAILS

Formulated with Advanced Resin Technology for outstanding adhesion, hide and color retention. Rich, beautiful appearance and a lasting finish. Excellent scrubability. Outstanding coverage and durability. Provides a dirt-resistant and mildew-resistant coating. Withstands the elements and resists frost, peeling, blistering, fading and cracking.

3 SURFACE PREPARATION

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections. New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

4 APPLICATION

Mixing of Paint: Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium custom-blended nylon/polyester brush, premium roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed. Do not apply when air and surface temperatures are below 50°F (10°C).

5 ENVIRONMENTAL HEALTH & SAFETY INFORMATION

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.